

Linear High Bay Light



Features

- Up to 140lm/W luminous efficiency
- DLC 4.0 qualified
- Low glare rating
- Meanwell HLG driver
- Available in 2, 3, 4, 5 feet lengths
- Housing made of 6063 aluminum
- IP65 rating and UL damp listed



Technical data

Housing	6063 aluminum
Lens	Diffused polycarbonate (white or clear)
CRI	>80
CCT	4000/5000/5700
Input Voltage (VAC)	100-277VAC 50/60Hz
Angle	120°
Mounting	Suspended or flush-mount



Specifications

Model	Dimensions	Power	Luminous Flux (lm)	Weight (kg/lb)
ELS-T6K0660xx	2ft x 7in x 3in	60W	7,800	3.9/8.6
ELS-T6K0680xx	2ft x 7in x 3in	80W	10,400	3.9/8.6
ELS-T6K09100xx	3ft x 7in x 3in	100W	13,000	5.4/12
ELS-T6K09120xx	3ft x 7in x 3in	120W	15,600	5.4/12
ELS-T6K12120xx	4ft x 7in x 3in	120W	15,600	6.8/15
ELS-T6K12160xx	4ft x 7in x 3in	160W	20,800	6.8/15
ELS-T6K15200xx	5ft x 7in x 3in	200W	26,000	8.1/17.9